

Imenertebat



 021-41525

 www.Imenertebat.org

 info@imenertebat.org





معرفی ایمن ارتباط



به نام خدا

• شرکت "ایمن ارتباط" بصورت سهامی خاص تاسیس گردیده و با بیش از 13 سال فعالیت مستمر و پویا، هم اکنون در زمره شرکتهای برتر در زمینه فروش و نصب سیستم های مخابراتی و حفاظتی شناخته می شود.

• شرکت ایمن ارتباط آماده انجام خدمات مشاوره رایگان، فروش و نصب و راه اندازی، آموزش، عقد قرارداد سرویس و نگهداری سیستمهای تلفن سانترال، دوربین های مدار بسته، دزدگیر اماکن، ضبط مکالمات گزارشات متنوع از تماسهای تلفن سانترال، لینک مراکز تلفن و..... میباشد.

• بدیهی است این مرکز مهندسی با بیش از 3000 مشتری در سراسر ایران می تواند با اتکاء به نیروی فنی و تکنسین های نصب، انواع خدمات نصب راه اندازی و پشتیبانی مراکز تلفن سانترال و سیستم های مدار بسته را در ظرفیت های مختلف، به شرکت ها و ادارات خصوصی و دولتی در سراسر کشور ارائه نماید.

• خط مشی کیفیت شرکت ایمن ارتباط

جلب اعتماد و رضایت کارفرمایان و مشتریان، بازنگری و بهبود مستمر کیفیت کارها و خدمات، ارتقاء مهارت کارکنان از طریق آموزشهای لازم

تعدادی از مشتریان ایمن ارتباط





GRANDSTREAM
CONNECTING THE WORLD

ایمن ارتباط



- Single SIP account
- Up to 2 Call appearances
- 3XML programmable soft keys
- EHS (Electronic Hook switch)
- 132*48 pixle LCD display

GXP1610



- Single SIP account
- Up to 2 Call appearances
- 3XML programmable soft keys
- EHS (Electronic Hook switch)
- 132*48pixle LCD display
- POE

GXP1615



- 2 SIP account
- Up to 2 Call appearances
- 3XML programmable soft keys
- EHS (Electronic Hook switch)
- 132*48 backlit graphical LCD dispaly
- HD wideband audio
- POE

GXP1625



- 2SIP account
- Up to 2 Call appearances
- 8 BLF keys
- Dual-switched Gigabit network ports
- 132*48 backlit graphical LCD dispaly
- 3XML programmable soft keys
- EHS
- POE
- HD wideband audio

GXP1628



- 3SIP account
- 3line keys
- HD audio on speakerphone and handset
- Dual-switched Gigabit ports,integrated POE
- 3 XML programmable context-sensitive sofkeys
- 8 dual-colored BLF/speed dial keys
- 4 way conferencing
- EHS

GXP1630

☎ 021-41525



www.imenertebat.org



- supports 3 line and 3 SIP accounts
- 4-way voice conferencing
- 2.8inch (320*240)color-screen LCD
- Dual Gigabit ports,integrated poe
- 8dual-colored BLF/speed-dial keys
- HD audio on the handset and speakerphone
- Integrated Bluetooth
- 4programmable context-sensitive soft keys

GXP2130



- supports 8 line and 4 SIP accounts
- 4XML programmable context-sensitive soft keys
- 4-way audio conferencing for easy conference calls
- 32digitally programmable and customizable BLF/spees-dial keys
- Dual switched,auto-sensing Gigabit ports,built-in poe
- HD audio on the handset and speakerphone:full duplex speakerphone
- Supports EHS compatible plantronics headsets
- Integrated Bluetooth

GXP2135



- supports 4 line and 4 SIP accounts
- 5-way voice conferencing
- 4.3inch (480*272)color-screen LCD
- 5programmable context-sensitive soft keys
- HD audio on the handset and speakerphone
- Compatible with GXP2200 LCD extension module(GXP2200 EXT)
- Integrated Bluetooth
- Supports EHS compatible plantronics headsets
- Dual Gigabit ports,integrated poe

GXP2140



- supports 6 line and 6 SIP accounts
- 5-way voice conferencing
- 4.3inch (480*272)color-screen LCD
- Dual Gigabit ports,integrated poe
- 5programmable context-sensitive soft keys
- HD audio on the handset and speakerphone
- 24dual-colored BLF/speed dial keys
- Integrated Bluetooth

GXP2160



- supports 12 line and 6 SIP accounts and 5-way voice conferencing
- 48on-screen digitally customizable B/speed-dial keys
- 4.8inch (480*272)color-screen LCD
- Supports up to for GXP2200EXT modules for BLF/speed-dial access to u to 160 contacts
- Dual Gigabit ports,integrated poe
- Integrated Bluetooth

GXP2170



- Supports 2 SIP accounts
- Up to 16 digital BLF Keys
- includes built-in dual-band WiFi support
- HD audio supporting all major codecs, including wideband codecs G.722 and Opus
- 240*340 pixle LCD display

GRP2612



- Supports 3 SIP accounts
- Up to 24 digital BLF keys
- Dual switched autosensing 10/100/1000 Mbps Gigabit ethernet ports with integrated PoE
- Swappable face plates to allow for easy logo customization
- 240*320 TFT color LCD
- POE

GRP2613



- Supports 4 SIP accounts
- Dual LCD screens with digital BLF keys
- HD audio, handset and speakerphone with support for wide-band audio
- Integrated dual-band 802.11 a/b/g/n/ac WiFi
- Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports
- Integrated POE & Bluetooth

GRP2614

☎ 021-41525



www.imenertebat.org



- 10 line keys with up to 5 SIP accounts
- 40 multi-purpose keys (MPKs)
- Integrated Bluetooth & POE & WIFI
- HD wideband audio
- a large 4.3 inch color LCD
- (integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)

GRP2615



- 6 line keys with up to 6 SIP accounts
- 4.3 inch color LCD screen
- Dual LCD screens with digital BLF Keys
- (48 virtual multi-purpose keys (MPKs)
- Integrated dual-band 802.11 a/b/g/n/ac Wi-Fi
- integrated Wi-Fi & POE, Bluetooth support

GRP2616



- 6 lines, 6 dual-color line keys with 3 SIP accounts
- 4 XML programmable context sensitive soft keys
- 24 digitally programmable & customizable BLF/fast-dial keys
- HD wideband audio, full-duplex hands-free speakerphone with advanced acoustic echo cancellation
- 5-way audio conferencing for easy conference calls
- Large phonebook capacity with up to 2000 contacts and call history with up to 500 records
- Supports EHS compatible Plantronics's headsets
- Built-in USB port for importing and exporting data only

GXP1760/1760W



- 8 lines, 8 dual-color line keys with 4 SIP accounts
- 4 XML programmable context sensitive soft keys
- 32 digitally programmable & customizable BLF/fast-dial keys
- 5-way audio conferencing for easy conference calls
- Dual-switched Gigabit ports (GXP 1782) or dual-switched 10/100 Mbps ports (GXP 1780) integrated POE
- Built-in USB port for importing and exporting data only
- Supports EHS compatible Plantronics's headsets

GXP1780/1782



- 128x384 backlit LCD display
- 20 programmable dual-color buttons per module, 2 pages per module (40 contacts total)
- BLF/speed dial
- Daisy-chain up to 4 modules for up to 160 contacts/extensions
- BLA (bridged line appearance)/SCA (shared call appearance), BLF (busy lamp field, standard or event list), Call Park/Pick-up, Speed Dial, Presence, Intercom, and conference/transfer/forward and more

GXP2200EXT



- 4.3 inch (272x480) TFT color LCD
- 20 per page (each module contains 2 pages, for up to 40 lines per module)
- Combine up to 4 daisy-chained modules for 160 contacts/extensions
- BLF, call park /pick-up, speed-dial, presence, intercom, voice conferencing transfer/forward and more

GBX20

☎ 021-41525

www.imenertebat.org



GRANDSTREAM
CONNECTING THE WORLD

ایمن ارتباط



- 6 lines 6 SIP accounts
- up to 6-way voice conferencing and 3-way video conferencing
- Dual-switched Gigabit ports and integrated WiFi (802.11b/g/n)
- 1 megapixel CMOS camera
- 4.3 inch (480x272) capacitive touch screen
- Runs Android version 4.2 and offers full access to the Google Play Store
- Bluetooth for headsets and pairing mobile devices, USB port, SD card slot

GXV3240



- 6 lines 6 SIP accounts, up to 6-way voice conferencing and 3-way video conferencing
- Runs Android version 4.2 and offers full access to the Google Play Store
- CMOS camera
- 7 inch (1024x600) capacitive touch screen
- Dual-switched Gigabit ports and integrated WiFi (802.11b/g/n)
- Bluetooth for headsets and pairing mobile devices, USB port, SD card slot

GXV3275



- 16 lines with up to 16 SIP accounts
- Built-in 1 mega-pixel CMOS tiltable camera for video calling with privacy wheel
- Runs on the Android 7.0 operating system
- Built-in Bluetooth for syncing with mobile devices and connecting Bluetooth headsets
- Dual-switched auto-sensing 10/100/1000Mbps network ports
- Integrated dualband Wi-Fi (2.4GHz & 5GHz)
- Built-in PoE/PoE+ for power and network connections

GXV3350



- 16 lines with up to 16 SIP accounts
- Built-in mega-pixel camera for video calling with privacy shutter
- Runs on Android 7.0 operating system
- Built-in Bluetooth for syncing with mobile devices and connecting Bluetooth headset
- Dual-switched auto-sensing 10/100/1000Mbps network ports
- Integrated dual-band WiFi (2.4GHz & 5GHz)
- Built-in PoE/PoE+ to power the device and give it a network connection
- 4-core 1.3GHz ARM Cortex A53 processor with 2GB RAM and 8GB eMMC Flash

GXV3370



- 16 lines with up to 16 SIP accounts
- Built-in 2 megapixel camera for video calling with privacy shutter
- Runs on the Android 7.x operating system
- Built-in Bluetooth for syncing with mobile devices and connecting Bluetooth headsets
- Dual-switched auto-sensing 10/100/1000Mbps network ports
- 8" (1280x800) capacitive 10-point touch screen IPS LCD

GVV3380

021-41525
www.imenertebat.org



- Supported by Grandstream's DP750 DECT Base Station
- 5 DP720 handsets are supported by each DP750
- Supports a range of 300 meters outdoors and 50 meters indoors from the DP750 base station
- Supports up to 10 SIP accounts per handset
- Full HD audio on both the speakerphone and handset
- 3.5mm headset jack, 3-way voice conferencing
- Automated provisioning options include TR-069 and XML config files

DP720

- Supports a range of up to 350 meters outdoors and 50 meters indoors when used with the DP752
- (300 meters outdoors when used with DP750)
- 1.8 inch (128x160) color LCD with 2 programmable soft keys
- Offers 20 hours talk time and 250 hours standby time
- Supports up to 10 SIP accounts and 10 lines per handset as well as 3-way conferencing
- Push-to-talk via a configurable button

DP722

- Supports a range of up to 400 meters outdoors and 50 meters indoors when used with the DP752 (300 meters outdoors when used with DP750)
- 2.4 inch (240x320) color LCD with 3 programmable soft keys
- Offers 40-hour talk time and 500-hour standby time
- Supports up to 10 SIP accounts and 10 lines per handset as well as 3-way conferencing
- Dedicated push-to-talk button, built-in proximity and accelerometer sensors for gesture control and alert notification
- HD audio on the speakerphone, handset, and headset jack

DP730

- Dual-band Wi-Fi with efficient antenna design and advanced roaming support
- 2 SIP accounts, 2 lines
- HD voice & dual MIC design with AEC and Noise Shield Technology
- Rechargeable 1500mAh battery, 6 hour talk time, 120-hour standby
- Configurable button for push-to-talk
- Micro USB port and 3.5mm headset jack

WP810

- Dual-band WiFi with efficient antenna design and advanced roaming support
- Bluetooth for syncing headsets and mobile devices (contacts and call transferring)
- HD voice & dual MIC design with AEC and Noise Shield Technology
- Rechargeable 1500mAh battery, 7.5 hour talk time, 150-hour standby
- Accelerometer and configurable button for push-to-talk, panic and other related functions
- Micro USB port and 3.5mm headset jack
- 2 SIP accounts, 2 lines
- Supports custom Android apps that fit the phone's screen/keys

WP820

- Up to 10 SIP accounts per system; up to 10 lines per handset; up to 5 concurrent calls per DECT system
- Supports a range of up to 300 meters outdoors and 50 meters indoors
- 3-way voice conferencing, full HD audio, integrated PoE
- Automated provisioning options include TR-069 and XML config files
- TLS and SRTP security encryption technology to protect calls and accounts
- Use with Grandstream's UCM series of IP PBXs for Zero Config provisioning

DP750

- Pairs with up to 5 of Grandstream's DP series DECT handsets via instant pairing using a dedicated pairing button
- Up to 10 SIP accounts per system; up to 10 lines per handset
- Support outdoor range of up to 400 meters with the DP730 or up to 350 meters with DP722/DP720 as well as indoor range up to 50 meters
- Supports Push-to-Talk and activity based on proximity and accelerometer sensors
- Automated provisioning options include TR-069 and XML config files

DP752

- Up to 2 concurrent HD calls
- Extends an additional range of 300 meters outdoors and 50 meters indoors for added mobility
- Automatic or manual association to DP750/DP752 base stations for easy use
- Supports Plug-n-Play features like auto association, auto region detection and seamless call handover
- Automated provisioning options include XML config files
- Ethernet connection provides PoE features

DP760



GRANDSTREAM
CONNECTING THE WORLD

ایمن ارتباط



- UCM6202 support up to 500 users and 50 concurrent calls
- Auto Discovery and Zero Configuration of Grandstream SIP endpoints
- Integrated 2 PSTN trunk FXO ports, 2 analog telephone FXS ports with lifeline capability and up to 50 SIP trunk accounts
- Gigabit network ports with Integrates PoE, USB, SD card
- Supports up to a 5-level IVR (Interactive Voice Response)
- Built-in call recordings server; recordings accessible via web user interface



UCM6202

- UCM6204 support up to 500 users and 75 concurrent calls
- Auto Discovery and Zero Configuration of Grandstream SIP endpoints
- Integrated 4 PSTN trunk FXO ports, 2 analog telephone FXS ports with lifeline capability and up to 50 SIP trunk accounts
- Gigabit network ports with Integrates PoE, USB, SD card
- Supports up to a 5-level IVR (Interactive Voice Response)
- Built-in call recordings server; recordings accessible via web user interface



UCM6204

- UCM6208 supports up to 800 users and 100 concurrent calls
- Auto Discovery and Zero Configuration of Grandstream SIP endpoints
- Integrated 8 PSTN trunk FXO ports, 2 analog telephone FXS ports with lifeline capability and up to 50 SIP trunk accounts
- Gigabit network ports with Integrates PoE, USB, SD card
- Supports up to a 5-level IVR (Interactive Voice Response)
- Built-in call recordings server; recordings accessible via web user interface



UCM6208

- Supports up to 2000 SIP endpoint registrations, up to 200 concurrent calls and up to 64 conference attendees
- 1GHz quad-core Cortex A9 processor
- 1GB DDR3 Ram, 32GB Flash
- 1 Integrated T1/E1/J1 interface, 2PSTN trunk FXO ports, 2 analog telephone/Fax FXS ports with lifeline capability
- Gigabit network ports with Integrates PoE, USB, SD card, integrated NAT router



UCM6510

021-41525



www.imenertebat.org



- 4 or 8 FXS ports with PSTN life line in case of power failure
- 2 10/100 Mbps network ports (switched or routed)
- Comprehensive codec support, caller ID, flexible dial plans and security protection
- Support for T.38 fax

GXV4008



- 4 or 8 ports
- 2 10/100 Mbps network ports
- Comprehensive codec support, caller ID, flexible dial plans and security protection
- Advanced security protection with SRTP
- Designed and tested for full interoperability with leading IP-PBXs, soft-switches and SIP-based environments
- PSTN Failover on power failure

GXV4104/8



GXV4248

- 16/24/32 FXS ports, GXW4248 includes 2 50-pin Telco connectors
- 1 Gigabit network port
- 132x48 backlit graphic display with support for multiples languages
- 4 SIP server profiles per system, independent SIP account per port
- Designed and tested for full interoperability with leading IP-PBXs, soft-switches and SIP-based environments
- Advanced security protection with SRTP/TLS/HTTPS

GXV4216/24/32/48



- Software configurable E1/T1/ J1 ports, support PRI, SS7, MFC R2
- Dual Gigabit auto- sensing RJ45 network ports with integrated NAT router
- Supports a wide- range of voice codecs, including Opus, G.722, G.729, iLBC, and more
- TLS and SRTP security encryption technology to protect calls and accounts
- Automated provisioning by HTTP/TFTP with XML config files
- Supports T.38 Fax for creating Fax-over-IP
- Supports multi- language voice prompts

GXV4500



- Supports 2 SIP profiles through 2 FXS ports and a single 10/100Mbps port
- TLS and SRTP security encryption technology to protect calls and accounts
- Automated provisioning options include TR-069 and XML config files
- Supports 3-way voice conferencing

ATAHT802



- Supports 2 SIP profiles through 2 FXS ports and dual Gigabit ports
- Includes a built-in NAT router which can handle routing speeds up to 100MBps
- TLS and SRTP security encryption technology to protect calls and accounts
- Automated provisioning options include TR-069 and XML config files
- Supports 3-way voice conferencing
- Failover SIP server automatically switches to secondary server if main server loses connection

HT812



- Supports 2 SIP profiles through 4 FXS ports and dual Gigabit ports
- Includes a built-in NAT router which can handle routing speeds up to 100MBps
- TLS and SRTP security encryption technology to protect calls and accounts
- Automated provisioning options include TR-069 and XML config files
- Supports 3-way voice conferencing

HT814



- Supports 2 SIP profiles and 8 FXS ports
- Strong AES encryption with security certificate per unit
- Automated & secure provisioning options using TR069
- 3-way voice conferencing per port
- Exceptional voice quality with wide-band HD codec
- Supports T.38 Fax for reliable Fax-over-IP

HT818



- 1.27Gbps wireless throughput and 2x Gigabit wireline ports
- Dual-band 2x2:2 MU-MIMO with beam-forming technology
- Support 802.3af Power-over-Ethernet (PoE)
- Support 450+ concurrent WiFi client devices
- Advanced QoS to ensure real-time performance of low-latency applications
- Up to 165-meter coverage range
- Up to 165-meter coverage range

GWN7600


- 1.27Gbps wireless throughput and 2x Gigabit wireline ports
- Dual-band 2x2:2 MU-MIMO with beam-forming technology
- Support 802.3af and 802.3at Power-over-Ethernet (PoE/PoE+)
- Support 450+ concurrent WiFi client devices
- Up to 300-meter coverage range
- Advanced QoS to ensure real-time performance of low-latency applications

GWN7600LR


- Support for up to 16 SSIDs per radio and up to 250+ concurrent WiFi clients
- Dual-band 3x3:3 MIMO technology and a sophisticated antenna design for maximum network throughput of up to 1.75Gbps and expanded coverage range of up to 175 meters
- Dual Gigabit ports with support for PoE/PoE+, USB port for future applications such as location based service and other IoT (Internet of Things) applications
- User friendly built-in provisioning controller (via Web interface) allows any GWN7610 to auto discover, auto-provision and manage networks of up to 50 GWN7610s without requiring separate controller hardware/software and without a single point of failure

GWN7610


- 1.17Gbps aggregate wireless throughput, 1x Gigabit and 3x 100Mbit wireline speed
- Up to 100 meters coverage range
- Self power adaptation upon auto detection of PoE/PoE+ and PSE
- Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate
- /random default password per device
- Support up to 80 Wi-Fi client devices

GWN7602


- 2.33 Gbps wireless throughput and 2 Gigabit wireline ports
- Dual-band 4x4:4 MU-MIMO technology
- Self power adaptation upon auto detection of PoE or PoE+
- Supports 200+ concurrent Wi-Fi client devices
- Up to 175-meter coverage range
- Advanced QoS to ensure real-time performance of low-latency applications
- Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/ random default password per device

GWN7630


- 2.33Gbps wireless throughput and 2x Gigabit wireline ports
- Dual-band 4x4:4 MIMO technology
- Self power adaptation upon auto detection of PoE/PoE+
- Support 200+ concurrent Wi-Fi client devices
- Up to 300-meter coverage range
- Advanced QoS to ensure real-time performance of low-latency applications
- Anti-hacking secure boot and critical data/control lockdown
- Flexibility of detachable/ changeable antenna for different application scenarios
- Embedded controller can manage up to 50 local GWN series APs; GWN. Cloud offers unlimited AP management

GWN7630 LR



- 1080p-Full-HD video
- up to 9-way video conferences
- PTZ camera with 12x zoom
- 9-way hybrid-protocol conferencing with no external MCUs/servers or extra software licenses
- support for 3 monitor outputs through 3 HDMI outputs
- Supports most SIP and H.323 video conferencing platforms

GVC3200



- Runs on Android 6.x operating system
- Sharp HD video resolutions up to 4k Ultra HD
- .Built-in Bluetooth for use with Bluetooth speakers/ microphones, keyboards, data exchange, etc
- Integrated dual band WiFi to pair
- Advanced camera with 16M pixel CMOS sensor
- FOV wideangle lens and ePTZ for easy camera view adjustments 90

GVC3210



- Powerful video resolutions up to 1080p
- Built-in RFID chip reader for keyless entry
- SIP video streaming to NVRs, video intercom stations, IP phones, or smart phones simultaneously
- Built with a metal casing to make it weatherproof and vandal resistant
- Built-in hemispheric camera allows for 180-degree wall-to wall coverage
- Supports motion detection
- Integrated PoE to power the device and provide a network connection
- Built-in microphone and speaker offers voice options and intercom functionality
- ONVIF Profile S compliant

GDS Accessories



USB RFID Card Reader



In-Wall Mounting Kit



RFID Card



RFID Key Fob

GDS3710



- HD audio options with up to 1.5m of audio input and 3m of audio output
- Built-in RFID chip reader for keyless entry
- Supports SIP calls to IP phones to facilitate communication
- Built with a metal casing to make it weatherproof and vandal resistant
- Integrated PoE to power the device and provide a network connection
- Built-in dual microphone and HD loudspeaker with advanced AEC offers intercom functionality

GDS3705

021-41525



www.imenertebat.org



Imenertebat

ايمن ارتباط

Yealink
EASY VOIP

MikroTik



021-41525



www.Imenertebat.org