


* نکته: این محصول بدون پایه ارائه می گردد.



2021-Q2

5 years Gold Guarantee

- پنج سال گارانتی طلایی بدون قید و شرط کی دی تی
- شش سال ضمانت پایداری کیفیت تصویر

سایر برتری‌ها:

- پشتیبانی از میکرو SD با ظرفیت 256Gb
- بدنه ضد آب و گرد و غبار با درجه IP44
- پشتیبانی از H.264+ / H.265+
- پشتیبانی از ONVIF ورژن 2.4
- قابلیت WDR, BLC, HLC, Defog

قابلیت‌های هوشمند:

- عبور از خط
- تشخیص حرکت
- ورود به منطقه

Camera	
Image Sensor	2MP Super Starlight (Sony-Japan) Cmos Sensor (1/2.8")
CPU	Dual-Core ARM Cortex-A7@900MHz
Lens	CS Mount - F:DC Iris/Auto Iris/Fixed Iris
Resolution	1920*1080 (2MP)
Available IR Range	N/A
D/N Filter	IR Cut Filter Switch (ICR)
Min Illumination	Color: 0.001 Lux(AGC on) - B/W: 0.0002 Lux(AGC on)
Angle of View	Depend On Lens
StarLight View	Yes-Color / Super Starlight
Picture Adjust	
Picture Function	120db WDR, DWDR, BLC, HLC, Defog, ROI
Shutter Speed	Manual (1/3 ~ 1/100.000), Auto
Image Parameter Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
Image Parameter	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264+(Ultra H.264), H.265+ (Ultra H.265)
Audio Compression	G.711A, G.711U
Frame Rate(60Hz)	30fps@1080P (WDR ON)
Transmission Stream	Triple Stream (Code Rate: 128kb-16mb)
Network	
Protocols	HTTPS, HTTP, TCP/IP V4-V6 , ICMP, RTSP, UDP, NTP, DHCP,DDNS, FTP, SNMP-V1-V2-V3, UPNP, SIP , NAT
Compatibility	Onvif Ver2.4 , Profile S, CGI, SDK, API
Max Users	10 Users
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer
Recording Software	Unlimited KDT CMS/VMS 128CH Per Monitor

Function	
Recording	FTP, NVR, CMS, NAS, SD Card
Record Type	Manual, Motion Detection, Smart Detection, Schedule
Alarm Triggers	All Intelligent Function
Event Action	Email, PTZ, Snapshot, Recording, Alarm Out, Buzzer, Pop up, Show Message
Intelligent Function	3 Smart Function Line Crossing, Entering The Area, Motion Detection
Interface	
Network	RJ45(10/100Mbps)+ LED Indicator on Port
Audio	Audio Out, Audio In
Alarm	Alarm Out, Alarm In
CVBS	Yes
Power	PoE LAN, DC In
Control	RS485
Memory Slot	Yes - Micro SD (256Gb Max)
General	
IP Rating	IP44 (Without Case)
Power Supply	DC12V ± 25% - AC24V ± 25%
POE Supply	IEEE802.3af-Max 8W(0.166A)
Web Language	English, Persian
Dimension	150*72*63 mm
Weight	636 g
Operation Humidity	Indoor: Up to 90%RH / Outdoor: Depend On Cover
Operation Temp	Indoor: -35°C ~ +65°C / Outdoor: Depend On Cover
Guarantee	
Product Guarantee	5 Years Gold Guarantee
MTBF	100K hrs min- MIL-HDBK-217F (25°)